



DISTRICT OF KITIMAT PURCHASING DEPARTMENT

206 ENTERPRISE AVENUE, KITIMAT, B.C., V8C 2C7 PH: (250) 632-8925 FAX: (250) 632-4650

INVITATION TO TENDER

Until the time designated in the attached schedule as the "Closing Time", the District of Kitimat will accept Tenders for furnishing to the District of Kitimat, the supplies or services described in the schedules attached hereto at the point or points designated therein. The said Tenders are subject to the Terms and Conditions of the Invitation to Tender, the Schedules, Instructions to Bidders, General Conditions, Specifications and any Special Conditions, Plans or Drawings attached hereto. All of which documents shall be initialed by the Bidder in the spaces provided.

TANDEM AXLE TRUCK 2018

STRAIGHT TRUCK, SANDER & SNOWPLOW APPLICATION

DATE OF TENDER: _____.

In compliance with the above Invitation to Tender, the undersigned offers and agrees if this Tender be accepted within 90 calendar days from the date of opening, to furnish or supply to the District of Kitimat, all or any part of the items upon which prices are stated, at the price set opposite each item, delivered to the designated point or points within the time specified in the schedule attached hereto.

COMPANY: _____.

ADDRESS: _____.

CITY: _____.

PROVINCE: _____ . **POSTAL CODE:** _____.

PHONE: _____ . **FAX:** _____.

SIGNATURE: _____ . **TITLE:** _____.

WITNESS(ES): _____.

The Bidder is a company incorporated under the law of _____.



EQUIPMENT OFFERED

It is the intent of the attached specifications to describe the minimum requirements for the equipment listed below. The materials and construction shall be first class, made to withstand the rigours of daily Municipal use. Any omissions from the specifications shall not relieve tenderers from the responsibility of furnishing a unit that is complete and ready to operate.

Table with 6 columns: ITEM, QTY, DESCRIPTION, MAKE, MODEL, UNIT PRICE. Rows include items (A) through (E) and a summary section with SUBTOTAL, ENVIRO LEVIES, GST, PST, and TOTAL.



GENERAL CONDITIONS OF TENDER

1. ACCEPTANCE

- 1.1. The right is reserved, as the interest of the Municipality may require, to reject any or all tenders and to waive any minor informality or irregularity in tenders received.
- 1.2. The Municipality reserves the right to accept any quantities less than those specified in the schedules at the prices offered, unless the tenderer specifies otherwise in his tender.
- 1.3. The District of Kitimat reserves the right to award the contract to other than the lowest tender received, following a full value analysis, if it perceives such to be in its best interest.
- 1.4. An acceptance forwarded to the successful tenderer within the time for acceptance specified in the tender results in a binding contract without further action by either party.

2. PRICES

- 2.1. Unit prices shall be shown for each unit on which there is a tender, and shall include all packing, crating, freight, cartage and shipping charges, and cost of unloading supplies at destination unless otherwise stated in this contract by the Municipality.

3. ALTERNATE TENDERS

- 3.1. The specifications describe the supplies which it is felt are necessary to meet the performance requirements of the Municipality. Tenderers desiring to tender on supplies which deviate from these specifications but which they believe to be the equivalent, are requested to submit alternate tenders on the goods which so deviate, however, **ALTERNATE TENDERS MUST BE CLEARLY INDICATED AS SUCH, AND DEVIATIONS FROM THE APPLICABLE SPECIFICATIONS PLAINLY NOTED.** All alternate tenders will be given due and utmost consideration. The tender must be accompanied by complete specifications of the supplies offered.

4. SIGNATURES

- 4.1. If an individual is making the tender, he shall print or type his name and address on the tender form and sign the same in the spaces provided. His signature shall be witnessed and the witness shall give his address.
- 4.2. If a partnership is making the tender, the name and address of the partnership shall be printed or typed on the tender form and the names of all members of the partnership shall be printed or typed in the space provided. The tender shall be signed by one or more of the partners in the following manner: for example, "Smith & Jones by John Jones a partner". The signature or signatures shall be witnessed and the witness or witnesses shall give their address or addresses.

- 4.3. If a company is making the tender, the name of the company and its place of business shall be printed or typed on the tender form and the tender form shall be signed by the person or persons authorized to sign the tender on behalf of the company, indicating the capacity in which they sign: for example, "John Doe Company Ltd., by John Smith, Secretary" or as the case may be.
- 4.4. Tenders signed by an agent must be accompanied by evidence of his authority.
- 4.5. The invitation to tender, conditions, specifications, schedules, and any other documents attached to the tender shall be initialed by the proper signing officer of the tenderer.

5. **TENDERS**

- 5.1. All prices and notations must be typewritten or written in ink. No erasures are permitted. Mistakes must be crossed out and corrections typewritten or written in ink adjacent thereto, and initialed in ink by the proper signing officer of the tenderer.
- 5.2. No tender, or modification thereof, received after the date and time fixed by the Municipality in the invitation to tender for receiving tenders will be considered.
- 5.3. In the case of mistakes in the extension of prices, unit prices will govern.
- 5.4. Tenders and modifications thereof shall be enclosed in sealed, return addressed envelopes addressed to the Municipal Purchasing Manager, 206 Enterprise Avenue, Kitimat, BC, V8C 2C7 and must be clearly marked "**TENDER FOR: TANDEM AXLE TRUCK 2018**", identifying the content of the tender.
- 5.5. Each tenderer will be given one (1) copy of the tender and shall return one (1) copy as instructed herein.

6. **CONDUCT OF CONTRACT**

- 6.1. The Municipal Purchasing Manager shall have the conduct of the contract.

7. **RESPONSIBILITY FOR SUPPLY**

- 7.1. Except as otherwise provided in this contract, the contractor shall be responsible for the supplies covered by this contract until they are delivered at the designated delivery point, regardless of the point of inspection; and the contractor shall bear all risks as to rejected supplies after notice of rejection.

8. **CONTRACTOR'S LIABILITY**

- 8.1. The contractor shall indemnify and save harmless the Municipality and its officers, servants, and agents from and against any and all claims relating to labour and material furnished for the work in connection with this contract and to inventions, copyrights, trademarks or patents and patent rights used or infringed by the contractor in the manufacture or supply of the supplies furnished thereunder, and from all such claims in the subsequent use and operation thereof after delivery to the Municipality.

- 8.2. The contractor shall be responsible for any and all damages or claims for damages for injuries or accidents done or caused by him or by any of his operations or by his employees or by any plant or machinery used in the performance of the contract, or which may happen by reason thereof or arising from any failure, neglect or omission on his part or on the part of his employees, to do or perform any or all of the several acts or things required to be done by him or them under and by this contract; and covenants and agrees to hold the Municipality harmless and indemnified from and against all such damages and claims for damage.

9. **LIENS**

- 9.1. The contractor, his surety and their respective heirs, executors, administrators, successors and permitted assigns shall fully indemnify the Municipality and all its officers, servants and employees from and against any and all liability or expenses by way of legal costs or otherwise in respect to any claim which may be made for a lien or charge at law or in equity or to any claim or liability under the Mechanic's Lien Act, or to any attachment for debt, garnishee process or otherwise.

10. **DEFAULT**

- 10.1. The Municipality may, subject to the provisions of article 10.3 below, by written notice of default to the contractor, terminate the whole or any part of this contract in any one of the following circumstances: if the contractor fails to make delivery of the supplies, or to perform the services within the time specified herein or any extension thereof; or if the contractor fails to perform any of the other provisions of this contract, or so fails to make progress as to endanger performance of this contract in accordance with its terms, and in either of these two circumstances, does not cure such failure within a period of ten (10) days, or such longer period as the Municipal Purchasing Manager may authorize in writing, after receipt of notice from the Municipal Purchasing Manager specifying any such failure.
- 10.2. In the event the Municipality terminates this contract in whole or in part as provided in article 10.1 of this clause, the Municipality may procure, upon such terms and in such manner as the Municipal Purchasing Manager may deem appropriate, supplies or services similar to those so terminated, and the contractor and his surety shall be liable to the Municipality for any excess cost for such similar supplies or services, provided, that the contractor shall continue the performance of this contract to the extent not terminated under the provisions of this clause.
- 10.3. The contractor shall not be liable for any excess cost if any failure to perform the contract arises by reason of strikes, lockouts, acts of God or of the public enemy, acts of the Municipality, fire or floods, or defaults of sub-contractors due to any such clauses unless the Municipal Purchasing Manager shall determine that the supplies or services to be furnished by the sub-contractor were obtainable from other sources in sufficient time to permit the contractor to meet the required delivery schedule.



11. **NOTICES**

- 11.1. Any notice required to be given in this contract shall be deemed to be duly given to the Municipality if sent by registered mail addressed to the Municipal Purchasing Manager at 206 Enterprise Avenue, Kitimat, BC, V8C 2C7 and to the contractor if sent by registered mail addressed to the contractor at the address hereinbefore set forth.

12. **DEFINITIONS**

- 12.1. The word "Municipality" means the District of Kitimat;
- 12.2. The words "Municipal Purchasing Manager" mean the person for the time being filling the office of Municipal Purchasing Manager for the District of Kitimat, or the person then acting as such;
- 12.3. The word "contract" means and includes the invitation to tender; the schedules; the general conditions; the specifications; the drawings; tender; award; surety bond and all other documents referred to in these general conditions, or attached hereto;
- 12.4. The word "contractor" or a pronoun in place thereof, means the person or persons who have undertaken to carry out this contract, including a corporation;
- 12.5. The word "supplies" means fixtures, chattels, equipment, goods, or other articles or things of whatsoever kind or nature required, intended or contemplated to be supplied and delivered to the Municipality pursuant to this contract.

**INSTRUCTIONS TO TENDERERS****1. CLOSING TIME: 2:00 PM., Wednesday, April 4TH, 2018.**

- 1.1. Tenders shall be enclosed and sealed in the return-addressed envelope provided, addressed to the Municipal Purchasing Manager, District of Kitimat, 206 Enterprise Avenue, Kitimat, BC, V8C 2C7. It is the sole responsibility of the tenderer to deliver his tender to the Municipal Purchasing Offices before the closing time.
- 1.2. Tenders must be submitted on the tender form and enclosed in the return-addressed envelope marked "**TENDER FOR TANDEM AXLE TRUCK 2018**" provided.
- 1.3. Tenders will be opened in public at 2:00 PM. on the closing date, in the conference room at the Public Works Yard located at 206 Enterprise Avenue, Kitimat, BC.
- 1.4. Response to this tender by email **WILL** be accepted. Please email purchasing@kitimat.ca
- 1.5. Tenders received after the noted due time will not be considered and will be returned unopened.
- 1.6. **Complete printed specifications and advertising literature must be attached to the tender form provided.**
- 1.7. Any deviations from the specifications shall be separately noted in the space provided on the specification sheets, with the separate information required attached.
- 1.8. Where any of the requirements listed are standard equipment on the particular equipment being tendered, this must be noted by writing "**AS SPECIFIED**" in the right hand column opposite the appropriate items on the specification sheets.

2. WITHDRAWAL

- 2.1. Tenders may be withdrawn by written notice only, provided such notice is received at the Municipal Purchasing Offices prior to the time set for the opening of tenders.

**SPECIAL CONDITIONS OF TENDER**

1. The tendered equipment shall be new and current production models of good commercial quality, treated to resist rust, corrosion and wear encountered in normal municipal works service and shall be complete with all necessary accessories for operation.
2. Response to this tender by fax **WILL NOT** be accepted.
3. New equipment will not be accepted until all conditions and tendered specifications have been met.
4. **WARRANTY**
 - 4.1. Warranties shall begin the day after delivery is considered complete and all deficiencies have been rectified.
 - 4.2. The District of Kitimat Mechanical Division is to be the warranty servicing agency for all minor warranty repair work. The successful tenderer is to prepare an agreement to cover this condition.
5. **DELIVERY**
 - 5.1. The equipment shall be delivered no later than **August 15th, 2018** to the District of Kitimat, Public Works Yard, 206 Enterprise Avenue, Kitimat, BC. Misleading delivery and installation information may affect future tender selection.
6. **PARTS AND SERVICE MANUALS**
 - 6.1. Complete and current service and parts manuals are required for all components for the complete units.



**SPECIFICATION SCHEDULE – ITEM A
TANDEM AXLE CAB & CHASSIS**

	<u>SPECIFICATIONS OFFERED</u>
◇ STATE MAKE OF CAB & CHASSIS :	◇
◇ STATE MODEL OF CAB & CHASSIS :	◇
◇ STATE MODEL YEAR OF CAB & CHASSIS :	◇

<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
◇ <u>G.V.W.R.:</u> <ul style="list-style-type: none"> • Approx. 66,000 LBS: • NOTE: to be labelled on both sides with GVW ◇ <u>WHEELBASE:</u> <ul style="list-style-type: none"> • Approx. 208” Wheel Base: ◇ <u>ENGINE AND PERIPHERAL COMPONENTS:</u> <ul style="list-style-type: none"> • Prefer Detroit Diesel or equivalent: • Minimum 400 HP @ 2100 RPM: • Specify Engine and Horse Power Offered: • Heavy Duty Cooling System: • Vertical Exhaust And Muffler, Located At The Right Hand Side Of The Cab, C/W Rain Cap And Heat Shield Screen: • Oil Filter: • Two Stage Cyclopac Air Intake Cleaner: • Thermo Clutch Type Fan At Radiator: 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<p>◇ <u>ENGINE AND PERIPHERAL COMPONENTS</u> <u>(continued)</u> :</p> <ul style="list-style-type: none"> • Extended Life Antifreeze In Cooling System Rated For -40⁰ C.: • Engine Block Heater Rated At 1,000 Watt, 120 VAC With The Plug Located Outside Of The Cab, Under Driver’s Door: • Fuel System Water Separator And Filter Mounted In The Engine Compartment: • Silicone Heater And Radiator Hoses: • Water Temperature And Oil Pressure Audio And Visual Warning System: • Low Hydraulic Oil Level Audio And Visual Warning System: • Low Water Level Indicator In Radiator: • Tachometer With Red Line Set At OEM Max Rpm: • Water, Oil, Fuel, Transmission Temperature, Dual Air Pressure And Voltmeter Gauges Located On The Dash: • Hour Meter: • Backup Alarm – state db • Engine shall be capable of performing Exhaust regeneration while in motion, as well as, prompted for a manual Exhaust Regeneration, if needed: • State Exhaust regeneration type DPF, DEF or other. If DEF, state exhaust fluid tank location and capacity. 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<ul style="list-style-type: none"> ◇ <u>POWER STEERING:</u> <ul style="list-style-type: none"> • Specify Make And Model Offered: ◇ <u>TRANSMISSION:</u> <ul style="list-style-type: none"> • Prefer Allison HD4560 Automatic Transmission: • Transmission Should Be Rated For 10% More Horse Power Than Supplied Engine Produces: • Heavy Duty Transmission Cooler: • Specify Make, Model And Gear Ratio Of Transmission Offered: ◇ <u>FRONT AXLE:</u> <ul style="list-style-type: none"> • Gross Axle Weight Rating Of 20,000 LBS. • Set Back Axle: • Heavy Duty Springs: • Heavy Duty Shocks: • Oil Fill For Hubs: • Specify Front Axle Offered: ◇ <u>REAR AXLES:</u> <ul style="list-style-type: none"> • Prefer Hendrickson HN-462 OR HAULMAX HMX 460 Suspension: • Gross Axle Weight Rating Of 46,000 LBS: • Rear Axle Ratio To Allow For Approx 100 KM/H: • Approx. 54” Spread: 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<ul style="list-style-type: none"> • Air Operated Inter-Axle Lock With Dash Mounted Indicator Light: • Driver Controlled Locking Rear Differential: • Specify Make And Model Offered: <p>◇ <u>DRIVELINE:</u></p> <ul style="list-style-type: none"> • Shall Be Sized For Engine Horsepower And Torque: • Specify Driveline Components Offered: <p>◇ <u>TIRES AND RIMS:</u></p> <ul style="list-style-type: none"> • Steel Disc Construction For All Wheels: Total of eleven (11) rims and tires, one will be a spare for the back axles. • Two (2) Only 22.5 x 12.5 front rims • Nine (9) Only, 22.5 X 8.25 rims for rear axles with a disc thickness Of 0.437”, Specify Type – Hub Piloted preferred: • Specify Make And Tread Type Of Tires Offered: <ul style="list-style-type: none"> • Two (2) Front: 425/65R22.5 Good Year G286A 20pr RPM 470 or equivalent • Nine (9) Rear: 11R x 22.5 Traction Tread Tubeless, Steel Belted Radial: <p>◇ <u>FRAME:</u></p> <ul style="list-style-type: none"> • Constant Depth Type Frame, Approximately 10” With Resisting Bending Moment Of 225,800 Nm (3 x 10⁶ IN.LBS.): • Supply Alloy Steel With Yield Point Of 760 Mpa (110,000 P.S.I.): • State The Size Of Reinforcement Used To Reach 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<p>The Required R.B.M. Of 3,421,000 IN.LBS:</p> <p>◇ <u>BRAKES:</u></p> <ul style="list-style-type: none"> • Full Air System, That Meets And/Or Exceeds All Legal Requirements: • Drain Valves At Tank Bottom With Levers Or Cables To Side Of Chassis For Operator’s To Drain Tanks: • Spring Brakes On Both Rear Axles: • Minimum 16.5 C.F.M. Compressor: • Parking Brake Valve On Dashboard To Be Push/Pull Type: • System Air Dryer, With Heater And Spin On Type Replacement Cartridge – state type: • ABS Braking System – state type: • Dust Shields on all axles: • “S” Cam Brakes With Automatic Slack Adjusters: • Size And Type Of Brakes Shall Be at a minimum: <ul style="list-style-type: none"> • Front: 16.5” X 6” Q+: • Rear: 16.5” X 7” Q+: <p>◇ <u>ALTERNATOR AND ELECTRICAL SYSTEM:</u></p> <ul style="list-style-type: none"> • 12 Volt, 130 Amp Minimum: • Plug-In Circuit Breakers Only - <u>NOT FUSES:</u> • Master Battery Disconnect Switch That Is Separate From The Ignition and Mounted Outside Cab, Behind Driver Side: 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<ul style="list-style-type: none"> • Grote 77083 Strobe Light Mounted In The Center Of The Cab Roof or equivalent: • Underbody Snowplow Illumination Light Mounted On The Left Hand Side: • Cab Strobe, Rear Sander strobe light, Sander Spread Illumination And Underbody Snowplow Lights Are To C/W Illuminated Rocker Switches Mounted In The Joystick Panel For The Sander Controls: • Rear strobe light, Sander Spread Illumination, marker lights and brake lights to be wired to back of truck to a truck mounted junction box. Then shall be wired to a trailer plug for easy sander plug in. • Additional Snowplow Lights mounted on the hood as to clear the front plow when raised. On/Off Switch to be in a convenient location for operator: <p>◇ <u>BATTERIES:</u></p> <ul style="list-style-type: none"> • Shall Be Of Sufficient Quantity And Size Required To Provide A Minimum Of 2,700 C.C.A. At -20⁰ C. In Accordance With SAE J537H Specifications: • Group 31 Batteries: • To Be Maintenance Free Design: • State Type Of Batteries Offered: <p>◇ <u>CAB SEATS:</u></p> <ul style="list-style-type: none"> • Driver’s Seat To Be High Backed, Cloth Covered, Air Suspension Type With Arm Rests: • Single Person Passenger Seat To Be Cloth Covered, Fixed Suspension Type: 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<ul style="list-style-type: none"> • Pelvic And Upper Torso Retractable Seat Belts Are Required For Both Seats: • Two (2) cloth seat covers: <p>◇ <u>CAB ACCESSORIES:</u></p> <ul style="list-style-type: none"> • Conventional Cab: • State Options For Hood Configurations: • Prefer grill be cut so as it remains stationary when hood is tilted in the forward position – so as not to interfere with the plow when installed. • Convenience Handles For Both Sides Of Cab And Also For Inside Of Doors: • Adjustable tilt steering column: • Air Horn With Snow Cover: • Air Conditioning: • Electric Horn: • Electric, Dual Speed, Intermittent Wind Shield Wipers With Wet Arm Windshield Washers: • Self-Canceling Turn Signal Lights, <u>NO EXCEPTIONS:</u> • Dual Sun Visors. • Cold Climate Package: • High Output Heater and defroster: • Dual, Heavy Duty, West Coast Style Mirrors, C/W Clearance Lights And Defrost Elements: • Two (2) Convex Mirrors: 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<ul style="list-style-type: none"> • High intensity head lights: • Daytime Driving Lights With Auto On/Off: • AM/FM Radio with MP3 and USB capabilities: • State Dimensions Of Cab Offered: <p>◇ <u>CAB SOUND LEVEL:</u></p> <ul style="list-style-type: none"> • Sound Level At Operator’s Position, Ear Elevation, Not To Exceed 85 dba, With Windows Closed, Ascending A 7% Grade With The Vehicle Loaded To The Registered G.V.W. • All Interior Noise Levels Shall Be Below The Workers’ Compensation Board Of B.C. Requirements. <p>◇ <u>FUEL TANK:</u></p> <ul style="list-style-type: none"> • Two Only, Step Type, Each With A Minimum Capacity Of 200 Litres (45 Gallons): <p>◇ <u>PAINT:</u></p> <ul style="list-style-type: none"> • Imoron Polyurethane Paint Or Equivalent: • Colour: Dupont Yellow #Du1560: • Frame And Undergear To Be Painted Black: • Fully Undercoated Cab, Chassis And Body: <p>◇ <u>BUMPERS:</u></p> <ul style="list-style-type: none"> • Front Only - Heavy Duty Painted Black C/W Two (2) Frame Mounted Tow Hooks: 		



<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<p>◇ <u>MANUALS:</u></p> <ul style="list-style-type: none"> • B.C. Motor Vehicle Inspection With A Certificate Of Acceptance And Window Decal MUST Be Supplied Before Arrival And On-Site Acceptance: • Current Service Manuals With Individual Detailed Electrical Drawings For The Completed Unit Shall Be Supplied As Follows: <ul style="list-style-type: none"> • Engine; • Transmission; • Differentials; • Steering Components; • Cab & Chassis; • Electrical System; • Current Parts Manuals For The Completed Unit Shall Be Supplied As Follows: <ul style="list-style-type: none"> • Engine; • Transmission; • Differentials; • Steering Components; • Cab & Chassis; • Electrical System; • Hydraulic System. • A Line Production Sheet Listing All Components Shall Be Furnished For The Completed Unit: <p>◇ <u>MISCELLANEOUS:</u></p> <ul style="list-style-type: none"> • Four (4) Sets Of All Keys Shall Be Supplied: • A B.C. Fire Marshall Approved 5 Lb. Rechargeable Dry Type Fire Extinguisher Shall Be Supplied: • Tool Box, Approximately 2' X 1' X 1', Mounted outside Of Cab in convenient location: 		



SPECIFICATION SCHEDULE – ITEM B

DUMP BOX 16 FT. INSTALLED WITH TARPING SYSTEM

<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<ul style="list-style-type: none"> ◇ <u>INSTALLED DUMP BOX:</u> <ul style="list-style-type: none"> • 16 Ft. Light Steel Dump Box With Cab Protector (To Be 14 Ft. From Back of Cylinder Tunnel to Inside Tailgate): • Minimum 25 Ton Single/Multi Stage Hoist Cylinder Mounted Above Frame Rails: • Wooden Sub-Floor: • Box Access Steps: • Sloped Tailgate: • Air Operated Tailgate locks: • Mud Flaps In Front And Behind Rear Wheels: • State Complete Specification Details For The Dump Box Offered: ◇ <u>INSTALLED TARPING SYSTEM:</u> <ul style="list-style-type: none"> • The Installed Tarping System Shall Be an Automatic Deployment utilizing 4 or 5 springs: • The system shall have manual rewind at ground level in a convenient location for the operator, without climbing on the dump box. • Tarp shall be of heavy duty quality to withstand asphalt temperatures of up to 400 degrees Fahrenheit and also have flaps to cover box sides when deployed: • State Tarp System Type and provide colour photos: 		



SPECIFICATION SCHEDULE – ITEM C

UNDERBODY ONE WAY SNOW PLOW

<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<p>◇ <u>INSTALLED ONE-WAY UNDERBODY SNOWPLOW:</u></p> <ul style="list-style-type: none"> • Preference Is For A Model Type, That Is Suitable For The Tandem Axle Truck Offered: • The Underbody Snowplow Shall Be Complete With Heavy Duty Plow Blade, Side Mount Plates With 2 7/8” Posts, Center Push Frame With Ram, 7/8” Heavy Duty Spring And Cutting Edge: • All Shall Be Painted Machinery Enamel Yellow: 		



**SPECIFICATION SCHEDULE – ITEM D
FRONT SNOWPLOW PUSH FRAME**

<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<p>◇ <u>INSTALLED FRONT SNOWPLOW PUSH FRAME:</u></p> <ul style="list-style-type: none"> • Preference Is For A Monroe Plow Mount, Suitable For A Monroe Model MPHS-35-66-12 One way Snowplow: • The Front Snowplow Push Frame Shall Be Complete with Lifting Device With 25” Front Plate, Lift Arm And Braces, 4” X 10” Double Acting Hydraulic Cylinder And High Mount Headlight Kit: • Plumbed And Valved for reversible front plow: • All Shall Be Painted Machinery Enamel Black: • Current front plow mount Henderson hitch (see attached drawing) Model Number 83126 hitch Serial Number HT-01567 or equivalent as long as existing Everest Front Reversing plow will fit. 		<p>: _____</p>



**SPECIFICATION SCHEDULE – ITEM E
HYDRAULIC SYSTEM**

<u>MANDATORY MINIMUM REQUIREMENTS</u>	<u>COMPLIANCE YES OR NO</u>	<u>STATE PRODUCT SPECIFICATION</u>
<p>◇ <u>INSTALLED HYDRAULIC SYSTEM:</u></p> <ul style="list-style-type: none"> • The Installed Hydraulic System Shall Be A System Suitable For Controlling The Dump Box Hydraulic Hoist, Front reversible Plow, Underbody Plow And Sander, With Joy Stick Controls To Be Mounted On A Pedestal For Easy Access By The Operator And The Sander Controls Shall Be Fully Adjustable And Related To Ground Speed; Preference is for Force America Controls: - HYDRAULIC LINES FOR SANDER SHALL RUN TO THE BACK OF THE TRUCK in convenient location. - Please provide current literature on Hydraulic system offered. • Truck Light Distribution Box: • Valve Enclosure And Reservoir With 10 Micron Absolute Return Filter, Access Cover, Breather And Sight Level Gauge And Shall Have A Minimum 45 Gallon Capacity: • State Complete Specification Details For The Hydraulic System Offered: 		<p>: _____</p>

<p>◇ <u>OTHER SPECIFICATIONS:</u></p> <p>⇒ <u>PARTS</u></p> <ul style="list-style-type: none"> • State hours of day parts service is available: • State location (city) of parts stock: • State approximate dollar value of parts stocked, applicable to the equipment tendered, at the above location, by your firm: 	<p>⇒ _____</p> <p>⇒ _____ City, Province.</p> <p>⇒ \$ _____</p>
--	---



⇒ **STANDARD WARRANTY**

- Period for Complete Machine:

⇒ _____ Months.

◇ **OPTIONAL ITEMS:**

- CAB & CHASSIS

- Please State Separate Pricing And Details For The Following Optional Items:

- Extended Warranty For Engine:
- Extended Warranty For Transmission:
- Heavy Duty Wiper Assembly and Blades:
- High intensity LED head lights:

⇒ _____ Months.

⇒ \$ _____

⇒ _____ Months.

⇒ \$ _____

⇒ \$ _____

⇒ \$ _____

- DUMP BOX

- Provide optional pricing for BATCHGATE style tailgate with three (3) chutes

Two (2) outside chutes to be 13” wide
 One (1) middle chute to be 17 ½” wide
 All three to have guillotine style doors

- * Provide optional pricing for High Lift style tailgate with three (3) chutes

Two (2) outside chutes to be 13” wide
 One (1) middle chute to be 17 ½” wide
 All three to have guillotine style doors

⇒ \$ _____

- * DUMP BOX TARPING SYSTEM

- * Provide optional pricing for Electrical Rewind:

⇒ \$ _____

- * UNDER BODY SNOW PLOW

- * Provide optional pricing for Two Way Operations

⇒ \$ _____

⇒ **DELIVERY**

- ⇒ **State delivery to destination (in calendar days) after order. Preferred date is August 15th or earliest possible date.**

⇒ _____ Days.